

## OSMO SYSTEM FOR VENTILATION CONTROL



## IN CASE OF 230V POWER SUPPLY CUT, INDEPENDENT OPERATION FOR UP TO 24 HOURS

LIFTING MOTOR FOR WINDOWS **12 V**TRACTIVE FORCE:

150KG\*

LIFT SYSTEM:

1 SHAFT FOR PULLEY

REF.4M10000





## **DESCRIPTION:**

Lifting motor electronically driven by high quality microcontrollers. Designed to create a natural or mechanical ventilation control equipment.

With built-in 12V battery (s), it allows to automate farms:

WITHOUT 230 V power supply - with generator sets and / or solar panels

**WITH** 230 V power supply, providing autonomy of up to 24 hours in the event of power outages at the facilities.

Protected from environmental conditions by its chassis and cover (galvanized / painted).

## **TECHNICAL SPECIFICATION:**

Motor: 12 V / 2 A

1 built-in battery 12 V / 5 Ah

Programmable travel of the windows

Speed: 3,5 min<sup>-1</sup> (rpm) \*

Dimensions length / width / height: 312 x 205 x 122 mm

Distance shaft-base: 55 mm

Weight: 9 kg

Maximum consumption (up / down): 2 A / 0,35 A

The flexible multi-conductor connecting sheath is not provided.

\* WITHOUT WEIGHT



CONSULT OSMO REGULATORS AND ACCESSORIES TO COMPLETE THE VENTILATION SYSTEM!