



OSMO SYSTEM FOR VENTILATION CONTROL

**IN CASE OF 230V POWER SUPPLY CUT ,
INDEPENDENT OPERATION FOR UP TO 24 HOURS**



**LIFTING MOTORS FOR CURTAINS 24 V
WITH MOBILE SUPPORT
TRACTIVE FORCE: 250Nm *
LIFT SYSTEM:
2 SHAFTS FOR TUBES
REF. 4M25003 / 3M12010M**



DESCRIPTION:

Lifting motor electronically driven by high quality microcontrollers. Designed to create a natural or mechanical ventilation control equipment.

The correct operation of the motor is guaranteed exclusively with an OSMOEUROPA power supply OFA** or battery box**. Otherwise, it does not work properly.

Important: complete the motor with a battery box ** OSMOEUROPA with the built-in 12 V battery(s) that allows to automate farms:**

WITHOUT 230 V power supply - with generator sets and / or solar panels

WITH 230 V power supply, providing autonomy of up to 24 hours in the event of power outages at the facilities.

** See menu – ACCESSORIES FOR MOTORS - at www.osmoeuropa.com

TECHNICAL SPECIFICATION:

Motor: 24 V / 2 A

Programmable travel of the windows

Dimensions length / width / height: 425 x 200 x310 mm

Weight: 6 kg

Maximum consumption (up / down): 2 A / 0,35 A

* WITHOUT WEIGHT

CONSULT OSMO REGULATORS AND ACCESSORIES TO COMPLETE THE VENTILATION SYSTEM!

